



JOMAX DRILLING (1988) LTD.

RIG #7E EQUIPMENT

DEPTH CAPACITY

Rating 5 400 m

DRILLPIPE SIZE

Size 127 mm

MAST

Make DRECO
 Model DAM 14225-1330
 Type CANTILEVER
 GNC 448,800 daN
 Hook Load 423,400 daN
 Lines 12
 Clear Height 43.29 m
 Base Width 7.6 m

SUBSTRUCTURE

Make DRECO
 Type BOX ON BOX ON BOX
 Casing Capacity 400,000 daN
 Setback Capacity 222,400 daN
 KB to Ground 8.96 m
 Clear Height 7.62 m

DRAWWORKS

Make OILWELL
 Model MODIFIED 840E
 Rating (1394 HP) 1 040 kw

DRAWWORKS POWER

Make GENERAL ELECTRIC
 Model 752HT
 Rating (1394 HP) 1 040 kw

ROTARY TABLE

Make OILWELL
 Model SA2750
 Static Load Rating 444,800 daN
 Table Opening 698 mm

MUD PUMP #1

Make LGF
 Model RSF1600
 Rating (1600 HP) 1 200 kw

MUD PUMP #2

Make LGF
 Model RSF1600
 Rating (1600 HP) 1 200 kw

MUD PUMP POWER

Make GULF ELECTRIC
 Model (2) GE752
 Rating (1000 HP) 746 kw

MUD TANKS (2)

Volume 215 m³
 Compartments 6

PREMIX TANK

Volume 87 m³

SHALE SHAKERS (2)

Make SWACO
 Model MONGOOSE PT

TRAVELLING BLOCK

Make OILWELL
 Model 6-60-H500
 Rating 445,000 daN

SWIVEL

Make NATIONAL
 Model P400
 Rating 356,000 daN

TOP DRIVE

Make TESCO
 Model ECI900
 Rating 500 Tons

PREVENTER STACK

Size 346 mm
 Rating 70,000 kPa
 Trim NACE

ANNULAR PREVENTER

Make TFI
 Model SPHERICAL

GATE PREVENTERS (1)

Make CAMERON
 Model U DOUBLE

GATE PREVENTERS (1)

Make CAMERON
 Model U

ACCUMULATOR

Make DRILLING CONTROL
 Model MB 140-15NIP

CHOKE MANIFOLD

Make VALVEWORKS
 Size 76 mm
 Rating 70,000 kPa
 Trim NACE
 Center Run DUAL

ENGINES (3)

Make CATERPILLAR
 Model 3512B
 Generator Size 1 225 kw

ENGINES (1)

Make CATERPILLAR
 Model 3508B Bi-Fuel
 Generator Size 750 kw

*** All specifications are rated at 100 %.