

RIG #2E EQUIPMENT

SCR:	Diesel Electric
PRIME MOVERS:	(4) Bi-Fuel Generators
TOP DRIVE:	350 Ton Varco IDS350
PRESSURE RATING:	7 500 Psi
DEPTH CAPACITY:	6 000 m
WALKING SYSTEM	Headwater Rail Style with 250' Umbilical Zipper System

Mast

Make:	Quality Fabricating
Model:	M142-21-750B
Type:	Cantilever
Hook Load:	333,600 daN w/12 lines
Clear Height:	43.30 m
Base Width:	6.40 m

Substructure

Make:	Quality Fabricating
Type:	Box on Box
Casing Capacity:	300,000 daN
Setback Capacity:	222,400 daN
KB to Ground:	7.47 m
Clear Height:	6.10 m

Drawworks

Make:	Rigmaster 1200E
Rating:	(1 394 HP) 1 040 kw
Powered By:	(2) 752HT

Mud Pumps (2)

Make:	Baoji
Model:	BSF1600
Powered By:	(2) Each. GE752
Power Rating:	(1 000 HP) 745 kw

Mud Tanks

Compartments:	7
Volume:	178.6 m ³

Premix Tank

Volume:	87 m ³
---------	-------------------

Shale Shakers (2)

Make:	Swaco Mongoose PT
-------	-------------------

Block

Make:	Oilwell A500
Rating:	445,000 daN



Top Drive

Make:	Varco IDS-350
Rating:	350 Tons

Preventer Stack

Size:	346 mm
Rating:	70,000 kPa

Engines (3)

Make:	Caterpillar
Model:	3512B Bi-Fuel
Generator Size:	1 225 kw

Engines (1)

Make:	Caterpillar
Model:	3508 Bi-Fuel
Generator Size:	682 kw

Boilers (2)

Make:	Williams & Davis - 100 HP
Type:	Bi-Fuel

Combination Water and Fuel Tank

Fuel Capacity:	48,885 Litres
Water Capacity:	56,000 Litres

ALL SPECIFICATIONS ARE RATED AT 100%